



Date of issue : 05/01/2005

Last. mod. date : 07/09/2009

Product code**02996 RI-140/100 GLOSS WHITE FLOOR TALKER ASP8A permanent GREY WKPE 1****Description**

Gloss white soft vinyl, very flexible and with a good conformability on the curved surfaces.

Solvent and eco-solvent ink-jet printing. Testing for suitability between media, printers and inks is always recommended prior to use.

Permanent grey solvent based adhesive with an excellent hiding power.

Applications for LFDP and as floor talker (to use with the overlaminating film RI-121/200).

Technical data**FACE MATERIAL**

Type	Soft vinyl
Colour and Finish	White, gloss
Weight	132g/m ²
Thickness	100μ

ADHESIVE

Reference	RI-ASP 8A grey
Type	Permanent acrylic GREY
Min. Appl. Temp.	+10°C
Service Temp.	-40°C/ +140°C
Shear	Excellent
Tack	Medium
Ultimate Adhesion	Very high

RELEASE BACKING

Type	1 side silicone coated 2 side PE coated Kraft
Colour and Finish	White
Weight	144g/m ²
Thickness	166μ

CHEMICAL RESISTANCE

Detergent	No effect (24 Hrs)
Gasoline	No effect (1 Hrs)
10% HCl	No effect (10 min)
SAE20 Motoroil	No effect (24 Hrs)
10% NH4OH	No effect (10 min)

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

All values presented in pdf data sheet are typical. Ritrama's data sheets provide only the general characteristics of the Product. It is the responsibility of the Customer and/or End User to determine that the Product is fit for the purpose for which the Customer and/or End User wish to use it. Ritrama can give no guarantee beyond the information given in the data sheet.