



Date of issue : 05/01/2005

Last. mod. date : 17/03/2009

Product code**03097 RI-6480 ANTIGRAFFITI UV SCREEN PROTECTED CLEAR ASP 8A permanent****Description**

Non top coated polyester with very good transparency (low haze) and with UV screening characteristics.

Not printable.

Permanent acrylic adhesive with excellent performance even at extreme outdoor conditions, and with very high UV protection characteristics.

Offers extreme high clarity, very high UV resistance and also has excellent anti-graffiti properties.

Technical data**FACE MATERIAL**

Type	PET
Colour and Finish	Clear, gloss
Weight	25g/m ²
Thickness	20μ

ADHESIVE

Reference	ASP 8A permanent
Type	Acrylic permanent
Min. Appl. Temp.	+10°C
Service Temp.	-40°C/+140°C
Shear	Very high
Tack FTM9	15N/inch ²
FinAdh FTM2	7N/inch

RELEASE BACKING

Type	1 side siliconised polyester
Colour and Finish	Clear
Weight	46g/m ²
Thickness	30μ
Transparency	>95%

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

All values presented in pdf data sheet are typical. Ritrama's data sheets provide only the general characteristics of the Product. It is the responsibility of the Customer and/or End User to determine that the Product is fit for the purpose for which the Customer and/or End User wish to use it. Ritrama can give no guarantee beyond the information given in the data sheet.