

Vision Soft Coated Vesta Weave



dpm

digital print media

Technical Data Sheet

Vision Soft Coated Vesta Weave

With INKTeX+BS® finishing for direct print, with flame retardant treatment,

Material	100 % Polyester
Stock widths	310 cm
Finishing	Rolled on paper cores
Ecology	Öko-Tex Standard 100, product class IV

Weight

acc. to DIN EN 12127	115.00	[g/m ²]	+ - 3	[%]
----------------------	--------	---------------------	-------	-----

Shrinkage

Heat Shrinkage, 195 °C, 90 sec,
lengthwise

acc. to AA 25-02	max. -2.00	[%]	+ - 1	[%]
------------------	------------	-----	-------	-----

Heat Shrinkage, 195 °C, 90 sec,
crosswise

acc. to AA 25-02	max. -2.00	[%]	+ - 1	[%]
------------------	------------	-----	-------	-----

Tearing strength

Maximum tensile elongation, longitudinal
direction

acc. to DIN EN ISO 13934-1	45.00	[%]	+ - 20	[%]
----------------------------	-------	-----	--------	-----

Maximum tensile elongation, cross direction

acc. to DIN EN ISO 13934-1	45.00	[%]	+ - 20	[%]
----------------------------	-------	-----	--------	-----

Maximum tearing strength, longitudinal
direction

acc. to DIN EN ISO 13934-1	min. 250.00	[N/5 cm]		
----------------------------	-------------	----------	--	--

Maximum tearing strength, cross direction

acc. to DIN EN ISO 13934-1	min. 260.00	[N/5 cm]		
----------------------------	-------------	----------	--	--

Air Permeability

acc. to DIN EN ISO 9237	3900.00	[l/m ² s]	+ - 10	[%]
-------------------------	---------	----------------------	--------	-----

Fire Retardancy

EN13501



Digital Print Media, The Heights, Ibstone Road, Stokenchurch, Bucks, HP14 3BG
T : 01494 760 240 E : sales@dpm.com W : www.dpm.com