

Vision Flat Voile



dpm
digital print media

Technical Data Sheet

Vision Flat Voile

With INKTeX+BS® finishing for direct print, with flame retardant treatment,

Material	100 % Polyester
Stock widths	app. 310 cm
Finishing	Rolled on paper cores
Ecology	According to Öko-Tex Standard 100, product class II

Weight				
acc. to DIN EN 12127	52.00	[g/m ²]	+ - 5	[%]
Shrinkage				
Heat Shrinkage, 195 °C, 90 sec, lengthwise				
acc. to AA 25-02	-2.00	[%]	+ - 1	[%]
Heat Shrinkage, 195 °C, 90 sec, crosswise				
acc. to AA 25-02	-1.00	[%]	+ - 1	[%]
Tearing strength				
Maximum tensile elongation, longitudinal direction				
acc. to DIN EN ISO 13934-1	20.00	[%]	+ - 20	[%]
Maximum tensile elongation, cross direction				
acc. to DIN EN ISO 13934-1	30.00	[%]	+ - 20	[%]
Maximum tearing strength, longitudinal direction				
acc. to DIN EN ISO 13934-1	min. 110.00	[N/5 cm]		
Maximum tearing strength, cross direction				
acc. to DIN EN ISO 13934-1	min. 400.00	[N/5 cm]		



Digital Print Media, The Heights, Ibstone Road, Stokenchurch, Bucks, HP14 3BG
T : 01494 760 240 E : sales@dpm.com W : www.dpm.com