

Vision Recyclaflex Flag



dpm
digital print media

Technical Data Sheet

Vision Recyclaflex Flag

The knitted yarn is made from 100% post consumer waste recycled polyester and contains no virgin material.

Material	100 % Polyester			
Stock widths	app. 320 cm,			
Finishing	Rolled on paper cores			
Ecology	According to Öko-Tex Standard 100, product class IV			
Weight				
acc. to DIN EN 12127	110.00	[g/m ²]	+ - 5	[%]
Shrinkage				
Heat Shrinkage, 195 °C, 90 sec, lengthwise				
acc. to AA 25-02	-1.00	[%]	+ - 1	[%]
Heat Shrinkage, 195 °C, 90 sec, crosswise				
acc. to AA 25-02	-1.00	[%]	+ - 1	[%]
Tearing strength				
Maximum tensile elongation, longitudinal direction				
acc. to DIN EN ISO 13934-1	5.00	[%]	+ - 20	[%]
Maximum tensile elongation, cross direction				
acc. to DIN EN ISO 13934-1	20.00	[%]	+ - 20	[%]
Maximum tearing strength, longitudinal direction				
acc. to DIN EN ISO 13934-1	min. 320.00	[N/5 cm]		
Maximum tearing strength, cross direction				
acc. to DIN EN ISO 13934-1	min. 540.00	[N/5 cm]		
Fire retardancy	B1/EN13501			



Roseash Limited, The Heights, Ibstone Road, Stokenchurch, Bucks, HP14 3BG

T : 01494 760 240

E : sales@dpm.com

W : www.dpm.com