

Vision Anti Graffiti Overlaminare



dpm
digital print media

Technical Data Sheet Vision Anti Graffiti Overlaminare

Face Material

Gloss clear polyester film.

Type	Polyester
Colour and Finish	Gloss Clear
Weight	28 g/m ² ±10% ISO-536
Thickness	20 µ ±10% ISO 534-80

Adhesive

Extra permanent acrylic adhesive with excellent performance even at extreme outdoor conditions, and with very high UV protection.

Reference	Extra Permanent
Type	Acrylic extra permanent
Min. Appl. Temp.	+10°C
Service Temp.	-40°C/+140°C
Shear	Very high
Tack	15 N/25mm FINAT FTM9
Final Adhesion	7 N/25mm FINAT FTM2

Liner

Type	One side siliconised polyester
Colour and Finish	Clear
Weight	42 g/m ² ±10% PP-032 - ISO ISO 534
Thickness	30 µ±10% ISO 536
Transparency	>95% DIN 53 147-64

Applications

Offers extremely high clarity, very high UV resistance and also has excellent anti graffiti properties. Recommended for lamination on rough surfaces and inkjet printing.

*Outdoor vertical exposure: Up to 3 years.
The durability is measure from unprinted films only and they are based on exposure conditions from Zone 1 (Italy, France, Northern Europe and eastern Europe*

Printing Methods

*Not Printable.
Testing for suitability between media is always recommended before prior use.*

Shelf life

12 months, applicable only to the material delivered by DPM which has not undergone further processing, under the following **STORAGE CONDITIONS**:

This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.

Storage area must be dry and clean.

Keep the material in the original packaging when not used in order to protect it from dust and contamination.

Do not expose to direct sunlight or heat sources.



1993 - 2020

Roseash Limited, Unit B, The Heights Business Park, Ibstone Road, Stokenchurch, Bucks, HP14 3BG
T : 01494 760240 E : sales@dpm.com W : www.dpm.com