

# Vision Digi Flag.

## Technical Data Sheet

<b>Material</b>	100% Polyester	
<b>Stock Widths</b>	1030mm / 1600mm / 3200mm / 5100mm	
<b>Weight</b> acc. to DIN EN 12127	110gsm	+/- 3%
<b>Shrinkage</b> Heat Shrinkage, 195 °C, 90 sec, lengthwise acc. to AA 25-02	-1.00%	+/- 1%
Heat Shrinkage, 195 °C, 90 sec, crosswise acc. to AA 25-02	-1.00%	+/- 1%
<b>Tearing strength</b> Maximum tensile elongation, longitudinal direction acc. to DIN EN ISO 13934-1	25.00%	+/- 20%
Maximum tensile elongation, cross direction acc. to DIN EN ISO 13934-1	50.00%	+/- 20%
Maximum tearing strength, longitudinal direction acc. to DIN EN ISO 13934-1	min. 140.00	
Maximum tearing strength, cross direction acc. to DIN EN ISO 13934-1	min. 620.00	
<b>Air Permeability</b> acc. to DIN EN ISO 9237	1900.00 l/m <sup>2</sup> s	+/- 10%
<b>Flame Retardancy</b>	B1 / EN13501	
<b>Ecology</b>	According to Öko-Tex Standard 100, product class I	