

Vision Dense Flag - Black.

Technical Data Sheet

Material	100% Polyester	
Stock Widths	Upto 3100mm	
Weight acc. to DIN EN 12127	110gsm	+/- 3%
Ecology	According to Öko-Tex Standard 100,product class I	
Recycling	Level 4 suitable Level 5 suitable	
Ink Type	Transfer Printing	
Shrinkage Washing Shrinkage, 1x 40°C, length Tumbler acc. to DIN EN ISO 6330	max. -2.50%	
Washing Shrinkage, 1x 40°C, width Tumbler acc. to DIN EN ISO 6330	max. -2.00%	
Tearing strength Elongation at 100 N, longitudinal direction acc. to DIN EN ISO 13934-1	5.80%	+/- 20%
Elongation at 100 N, cross direction acc. to DIN EN ISO 13934-1	15.00%	+/- 20%
Maximum tensile elongation, longitudinal direction acc. to DIN EN ISO 13934-1	24.00%	+/- 20%
Maximum tensile elongation, cross direction acc. to DIN EN ISO 13934-1	47.00%	+/- 20%
Maximum tearing strength, longitudinal direction (min.) acc. to DIN EN ISO 13934-1	min. 250.00 N/5cm	
Maximum tearing strength, cross direction (min.) acc. to DIN EN ISO 13934-1	min. 250.00 N/5cm	
Air Permeability acc. to DIN EN ISO 9237	1770.00 /m ² s	
Flame Retardancy	B1 / EN13501	