

Dreamscape - Duralon Suede.

Technical Data Sheet

Description	PVC Free, olefin based, vinyl alternative. TYPE II commercial strength.	
Weight	457gsm	
Available Widths	1370mm	
Construction	2-Ply Fabric Backed, TPO / Polyolefin Printable Face	
Optimal White Point	Unprinted white base film should measure no more than 0.5DE from these Cielab values to ensure optimal printing conditions L*93.04 a* -0.27 b*-1.42 C*1.45 h° 259.25	
Packaging	3" core, wound print side out, wrapped in protective bag, shipped in heavy duty cardboard tube	
Application	Standard commercial wallcovering pastes/primers and techniques. For indoor use in environmentally controlled spaces.	
Ink Compatibility	For printers using UV Curable ink systems, Latex, UV Gel (not recommended for solvent)	
Type II Properties	Passes all criterion for WA 101 Type II properties including: <i>Break Strength</i> <i>Tear Strength</i> <i>Cold Crack</i> <i>Heat Aging</i> <i>Shrinkage</i> <i>Stain Resistance</i> <i>Coating Adhesion (Bond)</i> <i>Colorfastness</i> <i>Washability</i> <i>Scrubability</i> <i>Blocking</i> <i>Crocking</i>	
Specifications	CCC-408-D Type II WA-101 NFPA Life Safety Code 101 RED LIST FREE HPD available Declare Label	
Fire Test Rating	ASTM-E84 Tunnel Test EU Class Flame (EN15102) BS476 Parts 6&7 CAN/ULC-S102	Passed Class A Passed Class C, s2 d0 Passed all requirements Passed all requirements
Mold/Mildew	ASTM-G21 Specifications	Passed all requirements
Environmental	PVC Free, No Plasticizers, No Phthalates, No Formaldehyde, No Chlorine, No Halogen, No Heavy Metals including: Cadmium, Mercury, Lead, or Zinc, and No Ozone Depleting Chemicals. Prop 65 compliant No harmful off gassing Low VOC emitting	